

# UHD40

True to life detail - 4K Ultra HD projector



- **4K UHD resolution and HDR compatible**
- **Amazing colour - accurate Rec.709 colours, 2400 ANSI lumens**
- **Easy connectivity - HDMI 2.0, HDCP 2.2, S/PDIF, 2x 5W speakers**
- **Easy installation - vertical lens shift**

Immerse yourself in a world of Ultra HD. The UHD40 delivers the ultimate in home entertainment with impressive 4K cinema quality images. TV, gaming and movie fans can now enjoy excellent colour depth, crystal clear detail, and sparkling contrast for a stunningly immersive experience.



# Specifications

EAN: 5055387660373, Colour: White

<b>Display/image</b>	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	2,400 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
<b>Optical</b>	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 ~ 16.74
Lens shift	Vertical +10%
Native offset	105%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm <b>Outputs</b> 1 x Audio 3.5mm, 1 x S/PDIF <b>Control</b> 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RS232, 1 x 12V trigger
<b>General</b>	
Noise level (typical)	25dB
Noise level (max)	27dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	9 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	2
Watts per speaker	5W
In the box	Lens cap AC power cord Remote control 2x AAA batteries Basic user manual
Input lag	57.00ms
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	249W
Power consumption (max)	305W
<b>Weight and dimensions</b>	
Dimensions (W x D x H) mm	392 x 281 x 118
Gross weight	6.76 kg
Net weight	5.22 kg

