

## EH470

Full HD 1080p, Bright and Powerful









- Bright Full HD 1080p projector 5000 ANSI Lumens
- Ultimate Control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- Easy connectivity 2x HDMI + MHL, RJ45, USB Power, 12V Trigger
- Quality audio featuring 10W speaker

Give hassle free and cable free presentations from a USB stick using the built-in photo and document viewer. You can even give presentations wirelessly from a mobile device using the optional wireless dongle.

This Full HD 1080p projector is ideal for meetings and classroom.

Boasting ultra-bright images for optimum visibility and a wide range of inputs allow you to effortlessly connect to devices such as computers and tablets. Additionally a built-in 10W speaker enables clear and loud audio.



## **Specifications**

Resolution 1080p Full HD (1920x1080)

 Brightness
 5,000 lumens

 Contrast ratio
 20,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3

 Keystone correction - horizontal
 +/-25°

 Keystone correction - vertical
 +/-30°

 Horizontal scan rate
 15.375 ~ 91.146Khz

 Vertical scan rate
 24 ~ 85(120 for 3D)Hz

Uniformity 75%

**Screen size** 0.66m ~ 8.25m (25.9" ~ 324.9") diagonal

Lamp info
Light source type
Lamp watts
285
Lamp life bours (up to)

**Lamp life hours (up to)** 2500 (Bright), 4500 (Dynamic), 3500 (Eco), 4500 (Eco+)

 Optical

 Throw ratio
 1.39:1 ~ 2.09:1

 Projection distance (m)
 1.2m - 10m

 Zoom
 1.5

 Zoom type
 Manual

 Focal length (mm)
 20.7 ~ 31.05

 Native offset
 115%

Connectivity

3D compatibility

Operating system

compatibility

Connections Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 1.4a 3D

support + MHL, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A reader

Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm

Control 1 x USB-A wireless, 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x mini USB mouse/service

trigger, 1 x mini USB mouse/servic

 General
 29dB

 Noise level (typical)
 29dB

 Noise level (max)
 31dB

 PC compatibility
 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

 2D compatibility
 NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

 SECAM B/D/G/K/K/1, 4.25/4.4MHz /8/0/ip. 578/i/p

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italia

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese

**Operating conditions** 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Data remote with laser and mouse function

Speaker count 1
Watts per speaker 10W

In the box AC power cord, remote control, 2x AA batteries, basic user

manual

Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS

Optional wireless models QuickCast Bundle, QuickCast starter kit, WHD200, WUSB

Networking
LAN - control Yes
LAN - display Yes

 LAN - wireless networking
 Yes - optional

 Power
 Power supply

 100 ~ 240V, 50 ~ 60Hz

Weight and dimensions

 Dimensions (W x D x H) mm
 345 x 216 x 109

 Gross weight
 4.13 kg

 Net weight
 2.95 kg





