

ZW350e Compact high brightness laser projector





- Bright WXGA laser projector 4000 lumens and IP6X certified
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- Compact for easy installation 1.1x zoom, 360degree and portrait projection
- External power supply More reliability, portability and energy efficiency

The ZW350e is one of Optoma's most compact and hassle-free WXGA DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4,000-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹



An added benefit, the ZW350e features an external power supply offering more reliability, portability and energy efficiency.

Specifications

Specifications	
EAN: 5055387666382, Colour: White	
JPC: 796435 44 612 3, Colour:	White
Display/image	
Display technology	DLPTM
Resolution	WXGA (1280x800)
Brightness	4.000 lumens
Contrast ratio	300.000:1
Contrast ratio - dynamic	2.000.000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Displayable colours (millions)	1073.4
lorizontal scan rate	15 ~ 140Khz
/ertical scan rate	24 ~ 120Hz
Jniformity	75%
Screen size	0.51m ~ 7.62m (20" ~ 300") diagonal
Lamp info	0.0 mm 47.02mm (20 14 000) alagonar
Light source type	Laser
_ASER life	30.000 hours
Optical Throw ratio	1.54:1 ~ 1.72:1
Projection distance (m)	1m - 10m
Zoom	1.1 Manual
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.00
Native offset	112%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	
Noise level (min)	27dB
Voise level (max)	34dB
PC compatibility	
	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
-	IP6X
P rating	
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish, Vietnamese
24/7 operation	Turkish, Vietnamese Yes
360° operation	Yes
360° operation Operating conditions	Yes
360° operation Dperating conditions Remote control	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style
360° operation Operating conditions Remote control Speaker count	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1
360° operation Operating conditions Remote control Speaker count Watts per speaker	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W
360° operation Operating conditions Remote control Speaker count Watts per speaker	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord
360° operation Operating conditions Remote control Speaker count Watts per speaker	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W
000° operation Operating conditions Remote control Speaker count Vatts per speaker	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control
000° operation Operating conditions Remote control Speaker count Vatts per speaker n the box	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery
000° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual
060° operation Operating conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power supply Power consumption (standby)	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power Power consumption (standby) Power consumption (min)	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power work Power consumption (standby) Power consumption (min) Power consumption (max)	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W
360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W
24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm Gross weight Net weight	Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 3000m Card style 1 15W AC power cord Remote control 1x CR2025 Battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. ¹ Based on the comparison of the 2023 Optoma mainstream laser projectors and its previous generation. ² Comparison of 2023 Optoma mainstream laser projectors. 01112023021709