

X600

Bright and powerful XGA projector



- **Bright XGA projector - 6000 ANSI lumens**
- **Ultimate control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Extensive connectivity – 2x HDMI, DisplayPort, RJ45, 12v trigger**
- **Built-in speaker**

Exceptional brightness, excellent connectivity and amazing colour ensure the X600 is the perfect choice for any large venue or conference room.

Boasting a wide range of inputs, it is easy to connect to devices such as computers and tablets. It also has networking capabilities that make it easy to manage and control the projector remotely via RJ45.



Specifications

Display/image	
Display technology	DLP
Resolution	XGA (1024x768)
Brightness	6,000 lumens
Contrast ratio	10,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction - horizontal	+/-0°
Keystone correction - vertical	+/-30°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0,71m ~ 8,34m (28,01" ~ 328,38") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	310
Lamp life hours (up to)	2500 (Bright), 3500 (Dynamic), 4000 (Eco+)
Optical	
Throw ratio	1,8:1 ~ 2,1:1
Projection distance (m)	1,2m - 12m
Zoom	1,15
Zoom type	Manual
Focal length (mm)	26,9 ~ 29,84
Native offset	112%
Connectivity	
Connections	<p>Inputs 2 x HDMI 1.4a 3D support, 1 x DisplayPort, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x S-Video, 1 x Audio 3.5mm, 1 x Audio RCA L&R</p> <p>Outputs 1 x VGA, 1 x Audio 3.5mm</p> <p>Control 1 x RJ45, 1 x RS232, 1 x 12V trigger, 1 x USB-B service, 1 x 3D sync</p>
General	
Noise level (typical)	28dB
Noise level (max)	30dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	3W
In the box	AC power cord, remote control, 2x AA batteries, basic user manual
Optional wireless models	QuickCast Bundle, WHD200
Networking	
LAN - control	Yes
LAN - display	Yes
LAN - wireless networking	Yes - optional
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	290W
Power consumption (max)	350W
Weight and dimensions	
Net weight	3,6kg
Dimensions (W x D x H) mm	345 x 216 x 109

