

ZH400UST

Superb for signage - 20,000 hours full brightness**



- **Bright Full HD 1080p laser projector - 4000 ANSI Lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **20,000 hours maintenance-free laser light source at full brightness****
- **Dust resistant – Independently tested, IP5X certification for total reliability**

The ZH400UST is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a low total cost of ownership.

Weighing only 5.6kg, this projector can be mounted just centimetres away from a wall or surface and can project an image size of over 100 inches (254cm).

Supporting 24/7 operation and versatile orientation, the ZH400UST is a flexible, powerful and bright ultra short throw projector which makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	1080p Full HD (1920x1080)
Brillo	4.000 lumens
Ratio de contraste	100.000:1
Relación de aspecto nativo	16:9
Ratio de aspecto - compatible	4:3
Corrección Keystone-Vertical	+/-15°
Frecuencia de muestreo horizontal	15.3 ~ 91.1KHz
Frecuencia de muestreo vertical	24 ~ 85(120 for 3D)Hz
Uniformidad	80%
Tamaño de pantalla	2.21m ~ 2.59m (87" ~ 102") diagonal
Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	30.000horas
Óptica	
Distancia de tiro	0.25:1
Distancia de proyección (m)	0.45m - 0.59m
Tipo de zoom	Fija
Distancia focal (mm)	3.72
Offset nativo	120%
Conectividad	
Conexiones	<p>Inputs 2 x HDMI 1.4a / 3D , 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm, 1 x Audio RCA L&R</p> <p>Outputs 1 x VGA compartida con VGA2, 1 x Audio 3.5mm, 1 x USB-A power 2A</p> <p>Control 1 x RS232, 1 x RJ45, 1 x mini USB servicio, 1 x USB-A wireless</p>
General	
Nivel sonoro (típico)	30dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Seguridad	Security bar, Kensington Lock, Password protected interface
idiomas OSD / display	18 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Si
Disipación de calor	890BTU/hour
Altavoces	1
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB
Networking	
LAN - control	Yes
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	210W
Consumo energético (máx.)	330W
Peso y dimensiones	
Peso	5.6kg
Dimensiones (W x D x H)	382 x 310 x 124

