


LH160

The ultimate portable business projector



- **Bright 1080p LED projector – 1500 LED Brightness**
- **Truly portable - Built-in battery**
- **Easy to setup - Auto keystone and four corner adjustment**
- **Optional wireless presentations**

The LH160 is the brightest 1080p LED projector with built in battery. Designed as the ideal business tool for presentations on the go it features USB display from a mobile device, Bluetooth, HV keystone and four corner adjustment. You can also give wireless presentations from a mobile device using the free HDCast Pro app and optional wireless USB adapter.



Specifications

| | |
|---------------------------------------|--|
| Display/image | |
| Display technology | DLP |
| Resolution | 1080p Full HD (1920x1080) |
| Brightness (LED) | 1,500 LED brightness |
| Contrast ratio | 160,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3,16:9 |
| Keystone correction - horizontal | +/-20° |
| Keystone correction - vertical | +/-30° |
| Has vertical auto keystone correction | Yes |
| Horizontal scan rate | 15 ~ 93Khz |
| Vertical scan rate | 24 ~ 120Hz |
| Uniformity | 85% |
| Screen size | 0.47m ~ 2.84m (18.6" ~ 111.8") diagonal |
| Lamp info | |
| Light source type | LED |
| LED life | 30,000 hours |
| Optical | |
| Throw ratio | 1.2:1 |
| Projection distance (m) | 0.49m - 2.97m |
| Zoom type | Fixed |
| Focal length (mm) | 12.64 |
| Native offset | 100% |
| Connectivity | |
| Connections | Inputs 2 x HDMI, 1 x USB-A wireless Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm |
| General | |
| Noise level (typical) | 30dB |
| Noise level (max) | 32dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 24/7 operation | Yes |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Yes |
| Speaker count | 2 |
| Watts per speaker | 4W |
| In the box | Carry bag AC power cord Remote control 2x AAA batteries Basic user manual |
| Operating system compatibility | Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ |
| Optional wireless models | WHD200, WUSB |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Battery life | Up to 2.5 |
| Weight and dimensions | |
| Net weight | 2.2kg |
| Dimensions (W x D x H) mm | 280 x 192 x 57 |

