
## UHD65 True to life detail - 4K Ultra HD projector



- 4K UHD resolution and HDR compatible
- Amazing colour accurate Rec.709 colours, 2200
  ANSI lumens
- Fluid viewing PureMotion frame interpolation
- Easy installation vertical lens shift

Designed for home cinema rooms, the UHD65 offers unforgettable 4K

digital cinema quality images in the comfort of your own home. Incorporating Ultra HD 4K resolution, it brings movies to life with thrilling detail, colour and contrast – taking entertainment to the next level.







## **Specifications**

EAN: 5055387650039, Colour: Black

| EAN: 5055387650039, Colour: Black  |  |
|--|--|
| Display/image  |  |
| Display technology   | DLPTM  |
| Resolution   | UHD (3840x2160)  |
| Brightness   | 2,200 lumens   |
| Contrast ratio   | 1,200,000:1  |
| Native aspect ratio  | 16:9   |
| Aspect ratio - compatible  | 4:3  |
| Horizontal scan rate   | 31 ~ 135Khz  |
| Vertical scan rate   | 24 ~ 120Hz   |
| Uniformity   | 85%  |
| Screen size  | 0.67m ~ 7.68m (26.45" ~ 302.2") diagonal   |
| Lamp info  |  |
| Light source type  | Lamp   |
| Lamp watts   | 240  |
| Lamp life hours (up to)  | 4000 (Bright), 15000 (Dynamic), 10000 (Eco)  |
| Optical  |  |
| Throw ratio  | 1.39:1 ~ 2.22:1  |
| Projection distance (m)  | 1.3m - 9.3m  |
| Zoom   | 1.6  |
| Zoom type  | Manual   |
| Focal length (mm)  | 20.91mm~32.62mm/0.823"~1.284"  |
| Lens shift   | Vertical +15%  |
| Native offset  | 100%   |
| Connectivity   |  |
| Connections  | Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x   |
|  | VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A service  |
|  | Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power   |
|  | 1.5A, 1 x 12V trigger  |
|  | Control 1 x RS232, 1 x RJ45  |
| General  |  |
| Noise level (typical)  | 25dB   |
| Noise level (max)  | 27dB   |
| PC compatibility   | UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,<br>SVGA, VGA, Mac  |
| 2D compatibility   | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),<br>1080p(50/60Hz), 2160p(50/60Hz)   |
| Security   | Security bar, Kensington Lock, Password protected interface  |
| OSD / display languages  | 9 languages: English, French, German, Italian, Japanese,   |
|  |  |
| Operating conditions   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max  |
|  | Portuguese, Russian, Chinese (simplified), Spanish   |
| Remote control   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote   |
| Remote control<br>Speaker count  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2  |
| Remote control<br>Speaker count<br>Watts per speaker   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W  |
| Remote control<br>Speaker count<br>Watts per speaker   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2  |
| Operating conditions<br>Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,   |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual  |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br><b>Networking</b>   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual  |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br><b>Networking</b><br>LAN - control  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max attitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms   |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max attitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms   |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power supply  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max attitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes  |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power supply<br>Power consumption (standby)   | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes<br>100 ~ 240V, 50 ~ 60Hz<br>0.5W                 |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power supply<br>Power consumption (standby)<br>Power consumption (min)  | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes<br>100 ~ 240V, 50 ~ 60Hz<br>0.5W<br>249W         |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power supply<br>Power consumption (standby)<br>Power consumption (min)<br>Power consumption (max)                                     | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes<br>100 ~ 240V, 50 ~ 60Hz<br>0.5W                 |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power consumption (standby)<br>Power consumption (min)<br>Power consumption (min)<br>Power consumption (max)<br>Weight and dimensions | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes<br>100 ~ 240V, 50 ~ 60Hz<br>0.5W<br>249W<br>305W |
| Remote control<br>Speaker count<br>Watts per speaker<br>In the box<br>Input lag<br>Networking<br>LAN - control<br>Power<br>Power supply<br>Power consumption (standby)<br>Power consumption (min)<br>Power consumption (max)                                     | Portuguese, Russian, Chinese (simplified), Spanish<br>5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max<br>humidity 85%<br>Backlit home remote<br>2<br>4W<br>AC power cord, remote control, 2x AA batteries, lens cap,<br>basic user manual<br>80.00ms<br>Yes<br>100 ~ 240V, 50 ~ 60Hz<br>0.5W<br>249W         |







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 26082023083520