

# W402

Bright, powerful and business ready



- **Bright WXGA projector – 4500 ANSI lumens**
- **Crestron RoomView® – RJ45 control and monitoring**
- **Easy connectivity – HDMI, VGA and built-in 10W speaker**
- **Lightweight and portable - Carry bag included**



Project bright, vibrant widescreen presentations any time of day. Designed for meeting rooms and classrooms, the W402 boasts a long lamp life and energy-saving features which provide a low overall cost of ownership.

This projector has a built-in speaker, networking capabilities, Full 3D technology and HDMI connectivity. It is also lightweight so can be installed or taken on the move in the handy carry bag for off-site meetings.

## Specifications

EAN: 5055387600164, Colour: White

### Display/image

Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	4,500 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.92m ~ 7.65m (36.3" ~ 301") diagonal

### Lamp info

Light source type	Lamp
Lamp watts	260
Lamp life hours (up to)	3000 (Bright), 5500 (Dynamic), 5000 (Eco), 7000 (Eco+)

### Optical

Throw ratio	1.28:1 ~ 1.536:1
Projection distance (m)	1.2m - 12m
Zoom	1.2
Zoom type	Manual
Focal length (mm)	21.8 ~ 23.98
Native offset	112%

### Connectivity

Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x VGA (YPbPr/RGB), 1 x Composite video, 2 x Audio 3.5mm <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm <b>Control</b> 1 x RS232, 1 x RJ45, 1 x 3D sync, 1 x mini USB mouse/service
-------------	---

### General

Noise level (typical)	31dB
Noise level (max)	33dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	20 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	Carry bag AC power cord Remote control 2x AAA batteries Basic user manual

### Optional wireless models

QuickCast Bundle, QuickCast starter kit, WHD200

### Networking

LAN - control	Yes
---------------	-----

### Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	257W
Power consumption (max)	306W

### Weight and dimensions

Dimensions (W x D x H) mm	315 x 224 x 102
Gross weight	4.1 kg
Net weight	2.57 kg

