

# W341+

Widescreen, bright and portable

---



- **Bright WXGA projector – 3800 ANSI lumens**
- **Easy connectivity – 2x HDMI, VGA, USB Power**
- **Clear, powerful audio - 10W speaker**
- **Lightweight and portable**

Project your presentations in HD effortlessly any time of day with the bright W341+. Designed for meeting rooms and classrooms, this small projector boasts high brightness, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

Easy to connect to with two HDMI inputs, MHL, USB Power and a built-in speaker, this projector is perfect for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro (sold separately). Additionally, you can connect your laptop, PC or Blu-ray player for clear projected images with sound. This portable and lightweight projector can be installed or taken on the move for off-site meetings or a friends house with the optional carry bag (sold separately).

# Specifications

<b>Display/image</b>	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	3,800 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	16:9, 16:10
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1KHz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.68m - 8.04m (26.87in - 316.5in)(Diagonal)
<b>Lamp info</b>	
Light source	Lamp
Lamp watts	195
Lamp life (hours)	5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+), 10000 (Education)
Lamp life (education)	10,000 hours
<b>Optical</b>	
Throw ratio	1.55:1 - 1.73:1
Projection distance (m)	1m - 12m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.86 ~ 24
Native offset	112%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A <b>Control</b> 1 x RS232
<b>General</b>	
Noise level (typical)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control Battery Basic user manual
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	187W
Power consumption (max)	225W
<b>Weight and dimensions</b>	
Net weight	2.17kg
Dimensions (W x D x H) (mm)	298 x 230 x 965

