

ZH450

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -4500 lumens and IP6X certified
- Compact for easy installation 1.6x zoom, 360degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH450 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the ZH450 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

EAN: 5055387666825, Colour: White

UPC: 796435 44 659 8, Colour: White

Display/image

Display technology DLP™

Resolution 1080p Full HD (1920x1080)

Brightness 4.500 lumens Contrast ratio 300,000:1 2,000,000:1 Contrast ratio - dynamic 16:9 Native aspect ratio 4:3 16:9 16:10 Aspect ratio - compatible

Keystone correction -

+/-30°

horizontal Keystone correction - vertical +/-30° Displayable colours (millions) 1073.4 Horizontal scan rate 15 ~ 140Khz Vertical scan rate 24 ~ 120Hz Uniformity 75%

0.51m ~ 8.18m (20" ~ 322") diagonal Screen size

Lamp info

Light source type LASER life 30,000 hours

Optical

Throw ratio 1.4:1 ~ 2.24:1 Projection distance (m) 1m - 10m Zoom 1.6 Manual Zoom type 20.91 ~ 32.62 Focal length (mm) Native offset 116%

Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General

29dB Noise level (min) Noise level (max) 35dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz 2D compatibility

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) 3D Full 3D

Security Security bar, Kensington Lock, Password protected interface IP6X

IP rating

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, OSD / display languages

Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

Remote control Card style Speaker count 15W Watts per speaker

In the box AC power cord Remote control

1x CR2025 battery Basic user manual

Optional wireless models Power

External power supply, 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 119W Power consumption (max) 173W

Weight and dimensions

274 x 216 x 114 Dimensions (W x D x H) mm 4.2 kg Gross weight Net weight 3 kg



